


Sizes		CHOPOK R90 45 LD 450/450- S/450(L/P)	CHOPOK R90 45 LD 450/510- S/450(L/P)	CHOPOK R90 45 LD 450/570- S/450(L/P)	
1	A	mm	450		
2	F	mm	1100	1160	1220
3	C	mm	470		
4	DN	Ø mm	160		
5	B	mm	450	510	570
6	V	mm	505		
7	R	mm	450		
8	AA	mm			
9	H	mm			
10	J	mm	325 + /160/		
11	K	Ø mm	2x125		
12	L	Ø mm	100		
13	M	mm			
14	N	mm	50		

Basic design:

Thermodynamic Hearth
Segment chamotte lining (SO)
Glass Classic
Inox control grip-handle RP2
Environmentally friendly varnish



CHPOK R90-S/450 P



CHPOK R90-S/450 L

Technical parameters			
1	Nominal heat output	kW	7,0
2	Pressure required	Pa	12
3	Average efficiency	%	77,3
4	Average flue gas temperature	°C	262
5	Wood consumption	kg/h	2,6
6	Consumption of combustion air	m ³ /h	21
7	Emission of CO to 13% O ₂	%	0,1
8	Flue gas mass flow	g/s	9,1
9	Weight	kg	150
10	Required min. cross section for circulating air - INPUT	cm ²	225
11	Required min. cross section for circulating air - OUTPUT	cm ²	350
12	Three-component insulated chimney - active height 5 m	Ø cm	160
13	Character of building construction with fireplace insert	warm air convection	Yes
		heat storage without conv	Yes

Optional accessories:

Cover frame (KR)
Glass Reflex (SR)
Black printed glass (SM)
Black printed glass Reflex (SMR)
External ashtray (VOP)
Lower hearth (ZO)
Convictional casing (DP)
Vertical heat-storing panel (AZ)
Heat accumulation quadrant (APO)
Divided door (LD2)

Test Method: ČSN EN 1322/A2:2007, FprEN16510-1, FprEN16510-2-2

Fireplace complies with the requirements: EN 13229, DIN +, BImSchV-Stufe 2, Commission Regulation (EU) č. 2015/1185 Ecodesign requirements

KOBOK reserves the right to change dimensions and parameters described in these sheets. The current edition can be downloaded from www.KOBOK.sk